



Dimensions are in inches

Modul/Module	m [mm]	5
Gangzahl der Schnecke Number of starts of the worm	[-]	1
Übersetzungs/Gear ratio	i [-]	86
Anzahl der Antriebe Number of drives	[-]	1
grey bore holes	(usually spaced)	
W	2 bore holes 1/2-1/3 UNC-0.787 deep	
X	4 grease nipples SAE-H11-9/16"-1/8" PTF	
Y	18 bore holes 5/8-11 UNC-1.181 deep	
Z	24 bore holes 0.709-0.394 deep / 5/8-11 UNC-1.181 deep	

Fett/grease: t-tecc Norplex LKP 2	
Anforderungen nach requirements as per	
DIN 51 825 - KP 2 P-20	
<u>Gehäuse Grundierung-unbearbeitete Flächen</u>	
<u>Primer housing-cruite cast surface</u>	
Farbtyp/paint: Einschichtlack/pure coat lacquer	
Produkt/product: Relonit 626-3K SGR	
Farbton/color: RAL 7033 zementgrau/RAL 7033 cement	
Lagerspiel/Clearance	
radiales Spiel	0-Vorspannung/ 0-preloaded
radial clearance	
axiales Kippspiel	0-Vorspannung/ 0-preloaded
axial tilting clearance	

[illegible]